

Fiberglass Patio Doors

Full Program Offering



**OAK WOODGRAIN
SMOOTH**





TABLE OF CONTENTS

- 3 Features & Benefits
- 4 Fiberglass Door Finishes
- 4 Jamb Options
- 5 Custom Paint Options

- Patio Door Collections:
- 6 Clear Lites
- 10 Obscure
- 12 Decorative
- 14 Impact
- 16 Simulated Divided Lites (SDL)

- 9 Energy Ratings Chart
- 18 Door Swing & Handing
- 19 Rough Opening Chart

Please see your store Associate for ordering assistance.

Customer Service: 800-375-8120
 Monday–Friday, 5:30 am to 5:00 pm (PST)

Email: info@featherriverdoor.com
 Warranty Tech Line: 888-533-2843

Warranty and Installation Instructions:
 Visit featherriverdoors.com
 – Go to Resources
 – Download a PDF copy

featherriverdoors.com

Distinctive character is brought to life through the hand-staining expertise of our craftsmen. Unique stain variations are to be expected—these are treasured elements of the real-wood look.

Pictures depicted in this brochure may have been graphically enhanced for illustration purposes. Printer and monitor limitations prevent exact color duplication for finished products shown in this brochure.

Top: Smooth—15-Lite Internal Grille Low-E Full Lite door painted Pure White
 Above: Smooth—1-Lite Low-E 3/4 Lite triple door painted Stormwind
 On the cover: Smooth—Mini Blinds Low-E Full Lite double door painted Gray Grey

FEATURES & BENEFITS

PREMIUM FIBERGLASS DOOR SYSTEMS

FIBERGLASS DOOR PANELS

Won't Dent, Rust, Rot or Crack

PVC JAMB SYSTEM

Full Non-Rot Protection
Ready to Paint

BALL BEARING HINGE

Prevents Door Sag and Hinge Wear
for Smooth Operation

MATCHING GLASS CAMING, SILL & HINGE FINISH†

Enhanced Look and Appearance

COMPOSITE ADJUSTABLE SILL WITH SCREEN TRACK

Limits Air and Water Infiltration
Composite System for Rot Resistance

COMPOSITE TOP & BOTTOM RAILS

Resists Rot and Insect Damage

FLUSH-GLAZED SYSTEM

FLUSH-GLAZED DESIGN

Clean Flush Door & Glass Frame System


LONG MOISTURE PATH

Sealant Protected by Multiple Barriers

DUAL FASTENING SNAP-FIT FRAME DESIGN

Distributes the Load Evenly
Provides an Even Seal
High DP Rating

FLUSH-GLAZED SYSTEM



SLIDING SCREEN DOOR

(Screens available on Inswing only)

Available on these Inswing Configurations:

- Center Hinge Unit = 1 Screen
- French Hinge Unit = 2 Screen
- Colors: White and Bronze

ENERGY EFFICIENCY

INJECTED POLYURETHANE FOAM CORE

Up to 5 times more energy efficient than wood
100% CFC Free (Environmentally Friendly)
Superior Density

FOAM COMPRESSION WEATHERSTRIP

Helps Seal Out Drafts

TIGHT INTEGRATION OF DOOR, GLASS AND FRAME

Superior Weather Resistance



Feather River proudly offers
ENERGY STAR® certified door
models in all 50 states.

SECURITY

WOOD LOCKBLOCK

Resists Forced Entry
Strengthens Lockset and Deadbolt Area

LAMINATED VENEER LUMBER (LVL) DOOR STILES WITH COMPOSITE CAP

Structural Integrity

SAFETY TEMPERED GLASS

OPTIONS

MULTI POINT LOCKING SYSTEM

- Lockset is 2-3/8" Backset
- Includes Active Handleset
- Dummy Handleset:
Option for French
Swing Units
- Handleset finish options:
Patina and Zinc
Must Match Sill Finish*



WARRANTY



†Inswing Units Only. All outswing units come with stainless steel hinges and zinc sills.

*If brass sill with an inswing unit: choose either finish option. All outswing units: zinc only.



ENERGY STAR® certified models
available for all 50 states

FEATHERRIVERDOORS.COM

FIBERGLASS DOOR FINISHES

SMOOTH

Unfinished – Ready to paint



Full Lite with Flush Glaze Frame



3/4 Lite Panel Profile

OAK WOODGRAIN

Unfinished – Ready to stain or paint



Full Lite with Flush Glaze Frame

JAMB OPTIONS

UNFINISHED WHITE WOODGRAIN PVC JAMB SYSTEM (Standard Option)

Standard option on both Woodgrain and Smooth Fiberglass

Unfinished

Ready to paint

Low Maintenance

- Will not rot or absorb moisture
- Insect resistant

Energy Efficient

Less heat transfer vs. common frame materials

Pre-Painted

Available as an option with any pre-painted door. Option available for exterior and interior color choice. Jamb color will match door color chosen or choose Painted White.



Widths:
4-9/16"
5-1/4"
6-9/16"

PRIMED FINGER-JOINTED WOOD JAMB (Option)

Primed white jambs are ready to paint and require regular maintenance over the life of the door.



Primed
White

Widths:
4-9/16"
5-1/4"
6-9/16"

Wood jamb comes standard with the Feather River Sill Key™ System. Sill Key™ doesn't allow jamb bottom to sit on sub floor or sill where it is susceptible to water damage.



PRE-COLORED WHITE PVC JAMB SYSTEM Widths: 4-9/16", 5-1/4" and 6-9/16" on both Woodgrain and Smooth Fiberglass

Note: Double Doors are standard with aluminum astragal, Oak woodgrain in bronze finish and Smooth with white finish.

CUSTOM PAINT OPTIONS



Add dramatic curb appeal without the mess and the hassle of having to paint yourself. It's easy with Feather River pre-painted doors. All you have to do is choose the color(s) you want.

Bright White Light 7757	Pure White 7005	Antique White 6119	Sun Fire 1141	<ul style="list-style-type: none"> • Durable paint finish • Two-color (interior and exterior) option available • Touch up paint included with all special orders • PVC jamb width options, see page 4
Gray Grey 7075	Stormwind 7072	Sage Mist 6178	Spring Coral 6606	
Elder Tree 2809	Burnt Cranberry 2801	Wine Red	Rich Cinnamon 7591	
Timeless Black 6258	Black Coffee 6006	Rich Soil 7510	Space Blue 6244	



Note: Colors shown are an approximate representation of the actual color. Actual finished color may vary in tone/shade (darker or lighter) from what is shown in brochure.

CLEAR LITES

Privacy Rating – 1

PRIVACY RATING (PR) **10**

1 Less private More private

Our glass collections are assigned a privacy rating based on the overall obscurity of the glass types used.


Styles & Finishes

SMOOTH Ready to Paint

OAK Unfinished – Ready to Stain or Paint

36" width full lites available in Smooth and Oak
 32" and 30" width full lites available in Smooth only
 All 3/4 lites available in Smooth only and 36" width
 12" width sidelites available in Smooth only

AVAILABLE CONFIGURATIONS



Double Door with sidelites and Quad units will need to be field mulled

6'8" Retro sized full lites and 3/4 lites

All door heights shown 6'8" | Widths shown next to door
 See page 4 for door finish and panel profile availability

✘ SDL options available, see page 16-17

▲ IMPACT option available, see pages 14-15


CUSTOM PAINT OPTIONS
 See page 5

Feather River offers ENERGY STAR certified door models in all 50 states. See page 9.




GRILLE OPTIONS

White Internal Grille Only



3/4" CONTOUR PROFILE



5/8" FLAT BAR PROFILE

- Flat bar profile is available for 10 and 15-Lite doors and the 5-Lite sidelite only
- 3/4 Lites only available with the contour profile

MINI BLINDS

(Single Operator)




- Single operator
- Raise/Lower function from single operator
- Standard 1/2" slats


10-LITE INTERNAL GRILLE LOW-E



Full Lite




5-LITE
INTERNAL
GRILLE
LOW-E



15-LITE INTERNAL GRILLE LOW-E



Full Lite



6-LITE INTERNAL GRILLE LOW-E



3/4 Lite



5-LITE
INTERNAL
GRILLE
LOW-E



9-LITE INTERNAL GRILLE LOW-E



3/4 Lite



More continued on next page

CLEAR LITES[®]

MINI BLINDS LOW-E



Full Lite



3/4 Lite

1-LITE LOW-E



Full Lite



3/4 Lite



ENERGY RATINGS CHART

Please visit our Resources page on featherriverdoors.com for the latest energy ratings information in the Performance Data section.

Flush-glazed Oak Woodgrain and Smooth Style Fiberglass Entry Doors and Sidelites

TYPE	SWING	GLAZING	3/4 Lite ≤ 1100 sq in		Full Lite > 1100 sq in	
			U-factor	SHGC	U-factor	SHGC
Fiberglass Door	Inswing & Outswing	Triple Pane—Laminated Impact Glass	0.27	0.20	0.30	0.26
		Triple Pane—Decorative/Obscure (5mm) Glass	0.26	0.20	0.30	0.27
		Dual Pane—Laminated Low E Impact Glass	0.25	0.19	0.27	0.25
		Dual Pane—Low E Wrought Iron	0.25	0.17	0.28	0.23
		Dual Pane—Low E-270 (Clear/Internal Grille)	0.23	0.13	0.26	0.16
		Dual Pane—Low E (Mini Blind UP)	N/A	N/A	0.34	0.22
		Dual Pane—Laminated Low E Impact (Mini Blind UP)	N/A	N/A	0.32	0.21

TYPE	SWING	GLAZING	3/4 Lite ≤ 391 sq in		Full Lite > 391 sq in	
			U-factor	SHGC	U-factor	SHGC
Fiberglass Sidelite	Inswing & Outswing	Triple Pane—Laminated Impact Glass	0.26	0.19	0.30	0.26
		Triple Pane—Decorative/Obscure (5mm) Glass	0.26	0.20	0.29	0.27
		Dual Pane—Laminated Low E Impact Glass	0.24	0.19	0.27	0.25
		Dual Pane—Low E Wrought Iron	0.25	0.17	0.28	0.23
		Dual Pane—Low E-270 (Clear/Internal Grille)	0.23	0.12	0.25	0.16
		Dual Pane—Low E (Mini Blind UP)	N/A	N/A	0.33	0.22
		Dual Pane—Laminated Low E Impact (Mini Blind UP)	N/A	N/A	0.31	0.21
Air Leakage ≤ 0.3 cfm/ft ²						

Will not qualify under ENERGY STAR 7.0 guidelines.

Will not qualify in the Northern and North-Central climate zones under ENERGY STAR 7.0 guidelines.


Does not meet 2023 Florida Energy Code Criteria for SHGC.

Updated 11-14-2023

Note: Ratings shown here are with PVC Jamb. Wood jamb ratings can be found in the Performance Data section of our Resources on featherriverdoors.com.

OBSCURE

Privacy Rating – PR

PRIVACY RATING (PR)  **10**
 1 Less private More private

Our glass collections are assigned a privacy rating based on the overall obscurity of the glass types used.


Styles & Finishes

SMOOTH  Ready to Paint

OAK  Unfinished – Ready to Stain or Paint

36" width full lites available in Smooth and Oak
 32" and 30" width full lites available in Smooth only
 All 3/4 lites available in Smooth only and 36" width
 12" width sidelites available in Smooth only


AVAILABLE CONFIGURATIONS*




* Sidelite option not offered for all glass designs
 Double Door with sidelites and Quad units will need to be field mulled

6'8" Retro sized full lites and 3/4 lites

All door heights shown 6'8" | Widths shown next to door
 See page 4 for door finish and panel profile availability

 SDL options available, see page 16-17

 IMPACT option available, see pages 14-15

Glass Collection Details booklet available on our website in the Resources section

 **CUSTOM PAINT OPTIONS**
 See page 5

Feather River offers ENERGY STAR certified door models in all 50 states. See page 9.



CROSS REED




Full Lite

SANDSTONE™



36
32
30

Full Lite



14
12



36

3/4 Lite

CORD



36
32
30

Full Lite



14
12



36

3/4 Lite

PRIVACY



36
32
30

Full Lite



14
12



36

3/4 Lite

DECORATIVE GLASS

Privacy Rating – PR

Brass – B | Patina – P | Zinc – Z | W – Wrought Iron

PRIVACY RATING (PR)

1	10
Less private	More private

Our glass collections are assigned a privacy rating based on the overall obscurity of the glass types used.


Styles & Finishes

SMOOTH Ready to Paint

OAK Unfinished – Ready to Stain or Paint

36" width full lites available in Smooth and Oak
 32" and 30" width full lites available in Smooth only
 All 3/4 lites available in Smooth only and 36" width
 12" width sidelites available in Smooth only

AVAILABLE CONFIGURATIONS*



* Sidelite option not offered for all glass designs

Double Door with sidelites and Quad units will need to be field mullied

6'8" Retro sized full lites and 3/4 lites

All door heights shown 6'8"
 Widths shown next to door
 See page 4 for door finish and panel profile availability

▲ SDL options available, see page 16-17

▲ IMPACT option available, see pages 14-15

Glass Collection Details booklet available on our website in the Resources section

CUSTOM PAINT OPTIONS
 See page 5

Feather River offers ENERGY STAR certified door models in all 50 states. See page 9.



BELLANTE™ | PR 8



3/4 Lite

PHOENIX™ | PR 8



3/4 Lite

MONROE™ | PR 6



3/4 Lite

SILVERDALE® | PR 7




Full Lite



3/4 Lite

STAR | PR 7




Full Lite



14
12
P

LAKEWOOD® | PR 6




Full Lite




3/4 Lite

PRESTON® | PR 7



Full Lite



3/4 Lite

SAPPHIRE™ | PR 7



Full Lite

36
P

MISSION POINTE™ | PR 8



Full Lite

36
Z

RIDGWAY™ | PR 8



Full Lite

36
Z

KINCAID™ | PR 8



Full Lite

36
P

LAKEMONT™ | PR 1



Full Lite

36
32
30
Z

15-LITE CLEAR BEVEL | PR 1



Full Lite

36
32
30
B
P
Z

SAN ANGELO™ | PR 8



Full Lite

36
32
30
W

TORINO™ | PR 8



Full Lite

36
32
30
W




IMPACT



DESIGNED TO MEET IMPACT REQUIREMENTS FOR "HVHZ" AREAS IN FLORIDA

HIGH PERFORMANCE DOOR & FRAME SYSTEM

- Integrated Door, Frame, and Glass for Superior Performance
- Reinforced Fiberglass Door Skin
- Dual-Fastening Snap-Fit Frame Design
- Safety Laminated Glass Interior / Safety Tempered Exterior
 - Interior: 1/8" x .090PVB x 1/8"



HIGH VELOCITY HURRICANE ZONE (HVHZ)

- Impact Rated Door Slab with Impact Rated Laminated Glass
- Dade and Broward Counties (FL)
- Must comply with specific DP Ratings
- Requires Impact Rated Door and Impact Rated Glass
- Outswing only

WIND BORNE DEBRIS AREA (WBD)

- Regular Non-Impact Door Slab with Impact Rated Laminated Glass
- Areas where wind speeds are 140 mph or 130 mph within 1 mile of coastal area
- Required to meet certain tests
- Inswing and Outswing

Doors will be available in the near future. Testing is ongoing for this program for FL and TX.

Styles & Finishes

SMOOTH

Ready to Paint

PR = Privacy Rating Patina – P | Zinc – Z

All door heights shown 6'8" | Widths shown next to door
See page 4 for door finish and panel profile availability

SDL options available, see pages 16-17

Glass Collection Details booklet available on our website in the Resources section

CUSTOM PAINT OPTIONS

See page 5

Feather River offers ENERGY STAR certified door models in all 50 states. See page 9.

Glass designs may vary slightly due to door shape and size



MICRO MINI BLINDS (Dual Operator)

- Raise/Lower function from dual operator
- Laminated impact glass
- Features 3/8" slats vs. 1/2" slats for modern look

AVAILABLE CONFIGURATIONS



AVAILABLE SIDELITE CONFIGURATIONS*




* WBD options available with certain glass collections

PRIVACY RATING (PR)

1	Less private	10	More private
---	--------------	----	--------------

Our glass collections are assigned a privacy rating based on the overall obscurity of the glass types used.

PRESTON® PR 7



Full Lite


3/4 Lite

SANDSTONE™ X
PR 8



Full Lite

CORD X
PR 8



Full Lite

PRIVACY X
PR 9



3/4 Lite | 36

Full Lite

1-LITE LOW-E X
PR 1



Full Lite

MINI BLINDS INTERNAL LOW-E
PR 1



Full Lite



3/4 Lite

FLORIDA BUILDING CODE: HVHZ TESTING INFORMATION 6/8 DOORS


DOOR TYPE	TESTING NUMBER	SWING	CONFIGURATION		
Glazed	FL# 20867.1	Outswing	DP Rating	± 60	± 55
			Impact	Yes	Yes
Glazed Mini Blind	FL# 37184.1 FL# 37184.2	Outswing	DP Rating	± 50	± 50
			Impact	Yes	Yes

For additional testing info for Feather River please visit the following:
 Visit: www.featherriverdoor.com/ Go to Resources/ Exterior Door Performance Data
 Visit: www.floridabuilding.org/ Go to Product Approval/ Find a Product/ Search Under Trinity Glass International
 Visit: www.tdi.texas.gov/ Look at Hinged Doors—Fiberglass/ Search Under Trinity Glass International


Additional Configurations and Testing may be available in the future

SIMULATED DIVIDED LITES (SDL)

Privacy Rating – PR



Our glass collections are assigned a privacy rating based on the overall obscurity of the glass types used.




Styles & Finishes

SMOOTH

Ready to Paint

Full lites available in 36", 32" & 30" widths
All 3/4 lites available only in 36" width

AVAILABLE CONFIGURATIONS




Double Door with sidelites and Quad units will need to be field mullled

6'8" Retro sized full lites and 3/4 lites

All door heights shown 6'8" | Widths shown next to door
See page 4 for door finish and panel profile availability

SDL FEATURES



1-1/8"
(1.125")


2-1/4"
(2.25")

3-1/2"
(3.5")

5-5/8"
(5.625")

Bar profile
for above widths

Bar profile
for above widths



- SDL bars are applied to both exterior and interior of glass
- SDL bars are non-removable
- SDL bar finish color and texture matches door
- All door and glass shown are also available without SDL bars

Glass Collection Details booklet available on our website in the Resources section


CUSTOM PAINT OPTIONS


See page 5

Feather River offers ENERGY STAR certified door models in all 50 states. See page 9.


FRAME PROFILE (Cross Section)

Smooth Flush Glaze






FULL LITE
 Colonial
 Grille Options:
 1-1/8" (shown)
 2-1/4"




36
 32
 30

4-Lite 6-Lite 8-Lite 9-Lite 10-Lite 15-Lite



FULL LITE
 Horizontal
 Grille Options:
 2-1/4"
 3-1/2"
 5-5/8" (shown)




36
 32
 30

4-Lite 5-Lite




3/4 LITE
 Colonial
 Grille Options:
 1-1/8"
 2-1/4" (shown)




36

4-Lite 6-Lite 9-Lite



3/4 LITE
 Horizontal
 Grille Options:
 2-1/4"
 3-1/2" (shown)




36

4-Lite 3-Lite 2-Lite



FULL LITE
 Horizontal
 Grille Options:
 1-1/8"
 2-1/4"
 3-1/2" (shown)










14
 12

5-Lite 4-Lite 3-Lite 2-Lite



DOOR SWING AND HANDING

DOOR CONFIGURATIONS




KEY


By choosing ONE configuration you will also be choosing:

- Door Activity
- Door Swing
- Door Handing

DOOR ACTIVITY VIEWED FROM TOP



SWING AND HANDING DETERMINED FROM OUTSIDE LOOKING IN



NOTE: Quad Units are built as two double units and shipped unattached. Brickmold is not offered. If you want more than one swinging door for your Quad Unit, please order two Double Units. Double Door with sidelites and Quad units will need to be field mulled.

ROUGH OPENING CHART




All measurements are in inches.




Threshold: Inswing Units- Threshold height is 1-3/8", which allows for approximately 1" opening clearance. If a spacer is needed under sill to allow for proper opening clearance, please adjust rough opening accordingly.

Double Door w/Sidelites: Must be field mullled (joined).

Quad Units: Built as two double units and shipped unattached. They must be field mullled (joined). Brickmold is not offered

HVHZ: Rough openings for HVHZ (Impact) are smaller than Rough Opening Chart sizes. Maximum space between actual unit size and rough opening is 1/2" in width and 1/4" in height.

INSWING		NOMINAL UNIT WIDTH	HEIGHT	PREHUNG UNIT W x H	ROUGH OPENING W x H	BRICKMOLD OPENING W x H	
		30	80	30 1/4 x 79 1/2	31 x 80	32 3/4 x 80 3/4	
		32	80	32 1/4 x 79 1/2	33 x 80	34 3/4 x 80 3/4	
		36	80	36 1/4 x 79 1/2	37 x 80	38 3/4 x 80 3/4	
		54 (12-30-12)	80	56 1/4 x 79 1/2	57 x 80	58 3/4 x 80 3/4	
		56 (12-32-12)	80	58 1/4 x 79 1/2	59 x 80	60 3/4 x 80 3/4	
		60 (12-36-12)	80	62 1/4 x 79 1/2	63 x 80	64 3/4 x 80 3/4	
		58 (14-30-14)	80	60 1/4 x 79 1/2	61 x 80	62 3/4 x 80 3/4	
		60 (14-32-14)	80	62 1/4 x 79 1/2	63 x 80	64 3/4 x 80 3/4	
		64 (14-36-14)	80	66 1/4 x 79 1/2	67 x 80	68 3/4 x 80 3/4	
			60 (30-30)	80	59 1/2 x 79 1/2	60 1/4 x 80	62 x 80 3/4
			64 (32-32)	80	63 1/2 x 79 1/2	64 1/4 x 80	66 x 80 3/4
			72 (36-36)	80	71 1/2 x 79 1/2	72 1/4 x 80	74 x 80 3/4
			90 (30-30-30)	80	89 1/8 x 79 1/2	89 7/8 x 80	91 1/8 x 80 3/4
			96 (32-32-32)	80	95 1/8 x 79 1/2	95 7/8 x 80	97 1/8 x 80 3/4
		108 (36-36-36)	80	107 1/8 x 79 1/2	107 7/8 x 80	109 1/8 x 80 3/4	
		84 (12-30-30-12)	80	86 1/2 x 79 1/2	87 1/4 x 80	89 x 80 3/4	
		88 (12-32-32-12)	80	90 1/2 x 79 1/2	91 1/4 x 80	93 x 80 3/4	
		96 (12-36-36-12)	80	98 1/2 x 79 1/2	99 1/4 x 80	101 x 80 3/4	
		88 (14-30-30-14)	80	90 1/2 x 79 1/2	91 1/4 x 80	93 x 80 3/4	
		92 (14-32-32-14)	80	94 1/2 x 79 1/2	95 1/4 x 80	97 x 80 3/4	
		100 (14-36-36-14)	80	102 1/2 x 79 1/2	103 1/4 x 80	105 x 80 3/4	
			60 (30-30)	80	59 3/4 x 79 1/2	60 1/2 x 80	62 1/4 x 80 3/4
			64 (32-32)	80	63 3/4 x 79 1/2	64 1/2 x 80	66 1/4 x 80 3/4
		72 (36-36)	80	71 3/4 x 79 1/2	72 1/2 x 80	74 1/4 x 80 3/4	
		90 (30-30-30)	80	89 1/2 x 79 1/2	90 1/4 x 80	92 x 80 3/4	
		96 (32-32-32)	80	95 1/2 x 79 1/2	96 1/4 x 80	98 x 80 3/4	
		108 (36-36-36)	80	107 1/2 x 79 1/2	108 1/4 x 80	110 x 80 3/4	
		120 (30-30-30-30)	80	119 1/2 x 79 1/2	120 1/4 x 80	122 x 80 3/4	
		128 (32-32-32-32)	80	127 1/2 x 79 1/2	128 1/4 x 80	130 x 80 3/4	
		144 (36-36-36-36)	80	143 1/2 x 79 1/2	144 1/4 x 80	146 x 80 3/4	

OUTSWING		NOMINAL UNIT WIDTH	HEIGHT	PREHUNG UNIT W x H	ROUGH OPENING W x H	BRICKMOLD OPENING W x H	
		30	80	30 1/4 x 78 3/8	31 x 78 7/8	33 1/4 x 79 1/8	
		32	80	32 1/4 x 78 3/8	33 x 78 7/8	35 1/4 x 79 1/8	
		36	80	36 1/4 x 78 3/8	37 x 78 7/8	39 1/4 x 79 1/8	
		54 (12-30-12)	80	56 1/4 x 78 3/8	57 x 78 7/8	59 1/4 x 79 1/8	
		56 (12-32-12)	80	58 1/4 x 78 3/8	59 x 78 7/8	61 1/4 x 79 1/8	
		60 (12-36-12)	80	62 1/4 x 78 3/8	63 x 78 7/8	65 1/4 x 79 1/8	
		58 (14-30-14)	80	60 1/4 x 78 3/8	61 x 78 7/8	63 1/4 x 79 1/8	
		60 (14-32-14)	80	62 1/4 x 78 3/8	63 x 78 7/8	65 1/4 x 79 1/8	
		64 (14-36-14)	80	66 1/4 x 78 3/8	67 x 78 7/8	69 1/4 x 79 1/8	
			60 (30-30)	80	59 1/2 x 78 3/8	60 1/4 x 78 7/8	62 1/2 x 79 1/8
			64 (32-32)	80	63 1/2 x 78 3/8	64 1/4 x 78 7/8	66 1/2 x 79 1/8
			72 (36-36)	80	71 1/2 x 78 3/8	72 1/4 x 78 7/8	74 1/2 x 79 1/8
			90 (30-30-30)	80	89 1/8 x 78 3/8	89 7/8 x 78 7/8	92 1/8 x 79 1/8
			96 (32-32-32)	80	95 1/8 x 78 3/8	95 7/8 x 78 7/8	98 1/8 x 79 1/8
		108 (36-36-36)	80	107 1/8 x 78 3/8	107 7/8 x 78 7/8	110 1/8 x 79 1/8	
		84 (12-30-30-12)	80	86 1/2 x 78 3/8	87 1/4 x 78 7/8	89 1/2 x 79 1/8	
		88 (12-32-32-12)	80	90 1/2 x 78 3/8	91 1/4 x 78 7/8	93 1/2 x 79 1/8	
		96 (12-36-36-12)	80	98 1/2 x 78 3/8	99 1/4 x 78 7/8	101 1/2 x 79 1/8	
		88 (14-30-30-14)	80	90 1/2 x 78 3/8	91 1/4 x 78 7/8	93 1/2 x 79 1/8	
		92 (14-32-32-14)	80	94 1/2 x 78 3/8	95 1/4 x 78 7/8	97 1/2 x 79 1/8	
		100 (14-36-36-14)	80	102 1/2 x 78 3/8	103 1/4 x 78 7/8	105 1/4 x 79 1/8	
			60 (30-30)	80	59 3/4 x 78 3/8	60 1/2 x 78 7/8	62 3/4 x 79 1/8
			64 (32-32)	80	63 3/4 x 78 3/8	64 1/2 x 78 7/8	66 3/4 x 79 1/8
		72 (36-36)	80	71 3/4 x 78 3/8	72 1/2 x 78 7/8	74 3/4 x 79 1/8	
		90 (30-30-30)	80	89 1/2 x 78 3/8	90 1/4 x 78 7/8	92 1/2 x 79 1/8	
		96 (32-32-32)	80	95 1/2 x 78 3/8	96 1/4 x 78 7/8	98 1/2 x 79 1/8	
		108 (36-36-36)	80	107 1/2 x 78 3/8	108 1/4 x 78 7/8	110 1/2 x 79 1/8	
		120 (30-30-30-30)	80	119 1/2 x 78 3/8	120 1/4 x 78 7/8	122 1/2 x 79 1/8	
		128 (32-32-32-32)	80	127 1/2 x 78 3/8	128 1/4 x 78 7/8	130 1/2 x 79 1/8	
		144 (36-36-36-36)	80	143 1/2 x 78 3/8	144 1/4 x 78 7/8	146 1/2 x 79 1/8	




Customer Service: 800-375-8120
Monday–Friday, 5:30 am to 5:00 pm (PST)

Email: info@featherriverdoor.com

Warranty Tech Line: 888-533-2843

Warranty and Installation Instructions can be found in the Resources section of our website

featherriverdoors.com



Smooth—Preston® Full Lite double door painted Pure White



D3077726-53E

4/24 BOK3HPOX © 2024 Trinity Glass International, Inc.

